

The Smartest Controls Should be Easy to Operate



Roll-2-Roll Technologies ARIS SCU5 controller is the brain of the Web Position Sensors and the Web Guiding Systems. The controller can be used for standalone sensing/measurement applications as well as for closed-loop control applications, with an appropriate actuator. Once the sensor(s) capture the raw images, ARIS SCU5 controller processes the information and sends appropriate measurement or feedback to the actuator. The controller also processes all the operator interface interaction as well as the interaction with external controllers through the

industrial Ethernet communication options. ARIS SCU5 is used with both the Web Position Sensors and Web Guiding Systems providing a variety of options as shown in the table in the following page.

GENERAL SPECIFICATIONS

Operator Interface	Optional color touchscreen	Output (Voltage)	± 10 V or 0 to 10 V
Languages	Language independent	Output (Current)	0 to 20 mA or 0 to 10 mA
Motor Driver	Microstepping or servo drive	Connectivity	Ethernet/IP, PROFINET
Motor	Servo or Linear hybrid stepper	Input Supply	24 V DC
Controller Frequency	50 to 200 Hz	Current	Less than 5 amps

BENEFITS

- **Increase productivity** with no setup and calibration after product changeover
- **Save time** with plug-and-play operation
- **Reduce waste** with high accuracy and high precision measurement
- **Reduce downtime** with increased sensor reliability
- **Save money** with an inexpensive alternative to vision systems
- **Save money** with a single solution for multiple sensing and guiding applications

To order (direct from factory):

By phone: **+1-888-290-3215 ext 01**

By e-mail: **sales@r2r.tech**

Online: **<https://r2r.tech/request-quotation>**

Your local contact is:

CONTROLLER OPTIONS

Following table shows the capabilities of the different controller option

Options	ARIS SCU5	ARIS SCU5 D	ARIS SCU5 C ⁴	ARIS SCU5 M	ARIS SCU5 MD	ARIS SCU5 MC ⁴ D
Input	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC	24 VDC
Application	Sensing	Sensing	Sensing	Web Guiding	Web Guiding	Web Guiding
Operator Interface	NO	YES			YES	YES
Analog output	YES	YES	YES	YES ¹	YES ¹	YES ¹
Voltage output	± 10 V ²	± 10 V ²	± 10 V ²	± 10 V ²	± 10 V ²	± 10 V ²
Current output	0 to 20 mA ³	0 to 20 mA ³	0 to 20 mA ³	0 to 20 mA ³	0 to 20 mA ³	0 to 20 mA ³
Motor Controller				YES	YES	YES
Actuator Included				YES	YES	YES
Current Consumption	< 2.5 Amps	< 3 Amps	< 2.5 Amps	< 5 Amps	< 5 Amps	< 5 Amps
Controller Frequency	50 - 200 Hz	50 - 200 Hz	50 - 200 Hz	50 Hz	50 Hz	50 Hz
Industrial Ethernet			YES			YES
Web browser dashboard			YES			YES
Remote Control			YES			YES
Diagnostics/Fault Info			YES			YES
Process two sensors	YES	YES	YES	YES	YES	YES
GO/NO GO	YES	YES	YES	YES ¹	YES ¹	YES ¹
Standalone System	YES	YES	YES ⁵	YES	YES	YES ⁵

¹ not a standard option but available upon request

² can be programmed to be ± 10 V or 0 to 10 V or ± 5 V or 0 to 5 V based on application requirement

³ can be programmed to be 0 to 20 mA or 4 to 24 mA or 0 to 10 mA based on application requirement

⁴ the industrial ethernet has two options C(E) for Ethernet/IP and C(P) for PROFINET

⁵ can be made standalone when not connected to a remote controller (PLC) or when set by remote controller (PLC)



Roll-2-Roll Technologies LLC
1110 S Innovation Way Dr
Stillwater, OK 74074
Phone: +1-888-290-3215
Support Email: experts@r2r.tech
Sales Email: sales@r2r.tech
Website: <https://r2r.tech>